

Anti-Aliasing Bandpass Filter case selection guide

Cut-Off Freq.	Connect Via	Series Number		
		Q34 & 36	Q40	Q56 & 70
1kHz to 99.9kHz	PCB Pins	20 <i>5.0" x 1.42" x 0.75"</i>	20 <i>5.0" x 1.42" x 0.75"</i>	20 <i>5.0" x 1.42" x 0.75"</i>
	SMA Female	720A <i>5.0" x 1.42" x 0.75"</i>	720A <i>5.0" x 1.42" x 0.75"</i>	720A <i>5.0" x 1.42" x 0.75"</i>
	BNC Female	720B <i>5.0" x 1.42" x 0.75"</i>	720B <i>5.0" x 1.42" x 0.75"</i>	720B <i>5.0" x 1.42" x 0.75"</i>
100kHz to 20MHz	PCB Pins	1335 <i>3.3" x 1.0" x 0.50"</i>	1335 <i>3.3" x 1.0" x 0.50"</i>	22 <i>5.0" x 1.42" x 0.50"</i>
	SMA Female	69A <i>3.0" x 1.0" x 0.75"</i>	69A <i>3.0" x 1.0" x 0.75"</i>	720A <i>5.0" x 1.42" x 0.75"</i>
	BNC Female	69B <i>3.0" x 1.0" x 0.75"</i>	69B <i>3.0" x 1.0" x 0.75"</i>	720B <i>5.0" x 1.42" x 0.75"</i>

PLEASE REFER TO THE CASE OUTLINE DRAWINGS FOR THE EXACT DIMENSIONS and MOUNTING INFORMATION.